



ARAMID FIBER SERVERS



- ✓ Ends are flown off the cobs and through manually adjusted tensioning devices
- ✓ Standard tension range is 150-400 grams, higher tension ranges are available
- ✓ Cob holders with quick locking collars are designed to accommodate cores of 3" and 3-11/16"
- ✓ Maximum cob package size is 12 pounds (5.4kg)
- ✓ Digital lay control allows following of master line or co-rotating use
- ✓ Optional casters and frame guards for portability on some models
- ✓ Main base is a precision machined heavy duty weldment
- ✓ Precision balanced aluminum back plate
- ✓ Custom orientation design for maximum application efficiency
- ✓ Available as stand-alone or complete line layout with payoff, capstan, tapers/binders and takeup

Model	# of Cobs	Main Drive (per section)	(RPM)	Max. Through Bore
PKS-8/8	16	2 HP	200	1.50"
PKS-12/12	24	2 HP	200	1.50"
PKS-15/15	30	2 HP	100	1.50"
PKS-30/30	60	5 HP	100	1.50"
PKS-60/60	120	7.5 HP	100	1.50"



11 Spruce Street,
Leominster, MA 01453 USA



1-800-241-4311



www.thermoplasticseng.com
sales@thermoplasticseng.com