



ROTATING CRADLE CABLERS



FEATURES

- ✓ Dual counterbalanced ball screw style traverse assemblies are AC driven
- ✓ Maximum 15° deflection angle from payoff to takeup (Model RTIU-800 has 20° maximum deflection angle)
- ✓ Heavy duty precision machined frame ensures accurate alignment and balance
- ✓ Dynamically balanced cradle for minimal vibration
- ✓ Pintle takeup design
- ✓ PLC based control system with digital lay control
- ✓ HMI Operating controls
- ✓ Line speed metering capstan with lay plate and closing die holder
- ✓ Variety of payoffs (neutralizing, drag and powered) and taping & binding heads available

Models	Reel Capacity	Max. Weight	Cradle RPM	Max. Diameter
RTTU-800	30" (800mm)	2500# (1136kg)	500	5/8" (15.9mm)
RTTU-1000	36" (1000mm)	3000# (1361 kg)	400	7/8" (22.2mm)
RTTU-1250	48" (1250mm)	5000# (2268kg)	250	1- 1/2" (38.1mm)
RTTU-1400	55" (1400mm)	5000# (2268kg)	150	2" (50.8mm)
RTTU-1600	64" (1600mm)	10000# (4536kg)	150	2- 1/2" (63.5mm)
RTTU-1800	72" (1800mm)	10000# (4536kg)	150	2-1 1/2" (63.5mm)

