



# CONCENTRIC TAPING HEADS



## FEATURES

- ✓ Heavy duty modular frame custom designed for required line height and line direction
- ✓ Fully guarded construction with sliding access door with magnetic interlock
- ✓ Custom sized tape guide tubes
- ✓ Multiple tape pad holder for quick changeover without breakout of main core
- ✓ Integral control panel
- ✓ Digital controller for automatic or manual lay length control
- ✓ Tape break switch
- ✓ Magnetic brake tension control with voltage indicator and run and stop tension adjust
- ✓ Optional light curtain sensor for constant tension control and low pad sensing
- ✓ Specialty units for traverse wound tape packages
- ✓ Binding head adapters available as option
- ✓ Concentric binding heads, tape let off stands and aramid fiber servers also available in various configurations

Standard Models	Standard Pad Size	Maximum RPM	Through Bore	Std. Drive System
CTH-14/3	14" OD x 3" ID x 1-1/2" wide	2500	1" (25.4mm)	1-1/2 HP DC
CTH-16/3	16" OD x 3" ID x 2" wide	2000	1" (25.4mm)	1-1/2 HP DC
CTH-18/3	18" OD x 3" ID x 2" wide	1750	1-3/4"(44.5mm)	2 HP DC
CTH-18/6	18" OD x 6" ID x 2" wide	1750	1-3/4"(44.5mm)	2 HP DC
TWTH-18	13" OD x 4" ID x 8" traverse	1500	2" (50.8mm)	1-1/2 HP DC
CTH-24/6	24" OD x 6" ID x 4" wide	800	3" (76.2mm)	5 HP DC

11 Spruce Street,  
Leominster, MA 01453 USA

1-800-241-4311

[www.thermoplasticseng.com](http://www.thermoplasticseng.com)  
 [sales@thermoplasticseng.com](mailto:sales@thermoplasticseng.com)