



VERTICAL DANCER ACCUMULATORS

FEATURES

- ✓ Fixed lower or upper sheave assemblies are supported
- ✓ Aluminum hard coated or UHMWPE sheaves designed from 8" to 22" root diameter with variety of groove diameters
- ✓ Digital linear position control signal to payoff or takeup
- ✓ Broken product limit switch and emergency line stop switch standard
- ✓ Pneumatic clamp complete with entry and exit roller guides, air cylinder, two rubber pads and a solenoid clamp control valve
- ✓ Large bore air cylinder and cable provides load tension with TEC air control system
- ✓ Custom accumulation lengths and tension ranges available
- ✓ Longer accumulation, horizontal styles available with torque motor tensioning control



Model	Sheaves	Sheave Groove Dia.	Air Cylinder Dia.	Max. Diameter	Height
HDDA-600/12/3	41 - 12"	1/2"	3"	25.0	18'
HDDA-460/16/3	47 - 16"	5/8"	3"	15.2	14- 3/4'
HDDA-300/22/8	33 - 22"	1-1 /4"	8"	100.0	15- 1/2'
HDDA-300/16/4	31 - 16"	15/16"	4"	35.0	14- 3/4'
HDDA-300/16/3	31 - 16"	15/16"	3"	23.3	14- 3/4'
HDDA-300/12/4	33 - 12"	5/8" or 3/4"	4"	35.0	13'
HDDA-300/12/3	33 - 12"	5/8" or 3/4"	3"	23.3	13'
LDDA-130/8/1.5	21 - 8"	5/8"	1-1 /2"	6.0	10'



11 Spruce Street,
Leominster, MA 01453 USA



1-800-241-4311



www.thermoplasticseng.com
sales@thermoplasticseng.com